



**MADE IN FRANCE
READY TO INSTALL**

TECHNICAL DATA / REF: ADV1698

| Setting | Power per zone (watts) | Setting | Power per zone (watts) |
|---------|------------------------|---------|------------------------|
| 1 | 25 | 17 | 750 |
| 2 | 50 | 18 | 800 |
| 3 | 75 | 19 | 850 |
| 4 | 100 | 20 | 900 |
| 5 | 150 | 21 | 950 |
| 6 | 200 | 22 | 1000 |
| 7 | 250 | 23 | 1050 |
| 8 | 300 | 24 | 1100 |
| 9 | 350 | 25 | 1150 |
| 10 | 400 | 26 | 1200 |
| 11 | 450 | 27 | 1250 |
| 12 | 500 | 28 | 1300 |
| 13 | 550 | 29 | 1350 |
| 14 | 600 | 30 | 1400 |
| 15 | 650 | 31 | 1450 |
| 16 | 700 | 32 | 1500 |

| | |
|---------------------|--|
| External structure | AISI 304 stainless steel |
| Cooking surface | Vitroc ceramic top GLASS |
| Control panel | Glass touches |
| Amp load | 13 A |
| Functions | On/Off, manual power and temperature setting (+/-) with 4 digits display, timer control and boost mode. From 30°C to 250°C. 3000W available on a cooking zone if the second one does not work. |
| Power supply | 230 V; 208/240 V ; AC 50 - 60 Hz |
| Standards | Complies with European standards for safety of electrical appliances, for EMC, for Rohs and SGS as well as with Intertek NSF & UL standards. |
| Details and options | Including a power cord and a washable filter (wash regularly). |

