

# Induc-NoLimit

by ADVENTYS

HOST 2017  
**SMART LABEL**




## MULTI-ZONE INDUCTION 32.000W MODULAR 800

Settings	Per zone
	Power (W)
1	25
2	50
3	100
4	150
5	200
6	250
7	300
8	350
9	400
10	450
11	500
12	550
13	600
14	650
15	700
16	750
17	800
18	850
19	900
20	1000
21	1100
22	1200
23	1300
24	1400
25	1500
26	1600
27	1700
28	1800
29	1900
30	2000

<b>Material</b>	Stainless steel and vitroceramic top glass.
<b>Inductors</b>	16 inductors covering all the vitroceramic surface.
<b>Controls</b>	Incremental encoder and 4 digits display. Power settings (W) or temperature settings (°C). 220 setting temperature levels : from 30 to 250°C.
<b>Power</b>	32.000 W.
<b>Amp load</b>	48A (+/-)10% per phases.
<b>Power supply</b>	Works between 250 and 490V / 40 and 70Hz. Compatible with TERA WATT energy optimizer. Generator cable length : 1.5m (custom cable in option).
<b>Standard</b>	Complies with European standards for safety of electrical appliances, for EMC, for Rohs and Intertek NSF & UL standards.
<b>Details &amp; options</b>	Compatible with TERA WATT & SICOTRONIC energy optimizer. Design and made in Burgundy (France).

